

Artistic Skylights conform to and exceed test requirements of the following criteria:
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on shingled roofs with minimum 3:12 pitch. These skylights mount directly over roof opening and require no curbs or metal flashings.

- Underlayment and backpan required for proper installation.
- Custom sizes are available upon request



Model G-PVCSR Available Sizes

Model #	B x B Dimensions	Glazing Type	QTY
G-PVCSR 2020	14 1/4" x 14 1/4" (362mm x 362mm)		
G-PVCSR 2052	14 1/4" x 46 1/4" (362mm x 1175mm)		
G-PVCSR 2828	22 1/4" x 22 1/4" (565mm x 565mm)		
G-PVCSR 2836	22 1/4" x 30 1/4" (565mm x 768mm)		
G-PVCSR 2852	22 1/4" x 46 1/4" (565mm x 1175mm)		
G-PVCSR 2860	22 1/4" x 55" (565mm x 1397mm)		
G-PVCSR 2876	22 1/4" x 69 1/2" (565mm x 1765mm)		
G-PVCSR 2896	22 1/4" x 89 1/2" (565mm x 2273mm)		
G-PVCSR 3636	30 1/4" x 30 1/4" (768mm x 768mm)		
G-PVCSR 3642	30 1/4" x 37" (768mm x 940mm)		
G-PVCSR 3652	30 1/4" x 46 1/4" (768mm x 1175mm)		
G-PVCSR 3660	30 1/4" x 55" (768mm x 1397mm)		
G-PVCSR 3676	30 1/4" x 69 1/2" (768mm x 1765mm)		
G-PVCSR 3696	30 1/4" x 89 1/2" (768mm x 2273mm)		
G-PVCSR 4242	37" x 37" (940mm x 940mm)		
G-PVCSR 4252	37" x 46 1/4" (940mm x 1175mm)		
G-PVCSR 4280	37" x 75" (940mm x 1905mm)		
G-PVCSR 5252	46 1/4" x 46 1/4" (1175mm x 1175mm)		
G-PVCSR 5260	46 1/4" x 55" (1175mm x 1397mm)		
G-PVCSR 5276	46 1/4" x 69 1/2" (1175mm x 1765mm)		
G-PVCSR 6060	55" x 55" (1397mm x 1397mm)		
G-PVCSR CUST.			
G-PVCSR CUST.			

Specifications:

Skylight shall be factory assembled Model No. _____ G-PVCSR as Manufactured by Artistic Skylight Domes Ltd., Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear low-E over clear. The skylight shall consist of rigid high-impact extruded vinyl base (superior in thermal conductivity to aluminum) which incorporates a high capacity, 18 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal, and 3" (76mm) mounting flange. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:
Contractor:
Architect:
Approved By:
Date:

Glazing Available

Glazing Type	Colour Code	Glazing Type	Colour Code
Clear/Low-E	Low-E	Clear/Laminated	Lami.
Bronze/Low-E	B/Low-E	Argon/Low-E	Low-E/Arg

