

## Fixed Dome (Triple Glazed) Aluminum Self Flashing Skylight

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on shingled roofs with minimum 3:12 pitch. These skylight mount directly over roof opening and require no curbs or metal flashings.

- Underlayment required for proper installation
- Custom sizes are available upon request



| Model T-SR Available Sizes |                   |                   |             |
|----------------------------|-------------------|-------------------|-------------|
| Model #                    | B x B Dimensions  |                   | Dome Colour |
| T-SR 2020                  | 14 1/4" x 14 1/4" | (362mm x 362mm)   |             |
| T-SR 2052                  | 14 1/4" x 46 1/4" | (362mm x 1175mm)  |             |
| T-SR 2828                  | 22 1/4" x 22 1/4" | (565mm x 565mm)   |             |
| T-SR 2836                  | 22 1/4" x 30 1/4" | (565mm x 768mm)   |             |
| T-SR 2852                  | 22 1/4" x 46 1/4" | (565mm x 1175mm)  |             |
| T-SR 2860                  | 22 1/4" x 55"     | (565mm x 1397mm)  |             |
| T-SR 2876                  | 22 1/4" x 69 1/2" | (565mm x 1765mm)  |             |
| T-SR 2896                  | 22 1/4" x 89 1/2" | (565mm x 2273mm)  |             |
| T-SR 3636                  | 30 1/4" x 30 1/4" | (768mm x 768mm)   |             |
| T-SR 3642                  | 30 1/4" x 37"     | (768mm x 940mm)   |             |
| T-SR 3652                  | 30 1/4" x 46 1/4" | (768mm x 1175mm)  |             |
| T-SR 3660                  | 30 1/4" x 55"     | (768mm x 1397mm)  |             |
| T-SR 3676                  | 30 1/4" x 69 1/2" | (768mm x 1765mm)  |             |
| T-SR 3696                  | 30 1/4" x 89 1/2" | (768mm x 2273mm)  |             |
| T-SR 4242                  | 37" x 37"         | (940mm x 940mm)   |             |
| T-SR 4252                  | 37" x 46 1/4"     | (940mm x 1175mm)  |             |
| T-SR 4280                  | 37" x 75"         | (940mm x 1905mm)  |             |
| T-SR 5252                  | 46 1/4" x 46 1/4" | (1175mm x 1175mm) |             |
| T-SR 5260                  | 46 1/4" x 55"     | (1175mm x 1397mm) |             |
| T-SR 5276                  | 46 1/4" x 69 1/2" | (1175mm x 1765mm) |             |
| T-SR 5280                  | 46 1/4" x 75"     | (1175mm x 1905mm) |             |
| T-SR 5296                  | 46 1/4" x 89 1/2" | (1175mm x 2273mm) |             |
| T-SR 6060                  | 55" x 55"         | (1397mm x 1397mm) |             |
| T-SR 6076                  | 55" x 69 1/2"     | (1397mm x 1765mm) |             |
| T-SR 6096                  | 55" x 89 1/2"     | (1397mm x 2273mm) |             |
| T-SR 7272                  | 67" x 67"         | (1702mm x 1702mm) |             |
| T-SR 7296                  | 67" x 89 1/2"     | (1702mm x 2273mm) |             |
| T-SR CUST.                 |                   |                   |             |
| T-SR CUST.                 |                   |                   |             |

**Specifications:**

Skylight shall be factory assembled Model No. \_\_\_\_\_ T-SR as Manufactured by Artistic Skylight Domes Ltd., Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight shall consist of corrosion resistant extruded aluminum base frame, 6063-T5 alloy, and 3" aluminum mounting flange with heliarc welded corners. The skylight base frame shall have 2" thermal insulation and an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 8 degree sloped condensation gutter with drainage to exterior, and co extruded rubber draft seal. Retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

|              |
|--------------|
| Project:     |
| Contractor:  |
| Architect:   |
| Approved By: |
| Date:        |

**Dome Colours Available**

| Dome Colour | Colour Code | Dome Colour | Colour Code |
|-------------|-------------|-------------|-------------|
| Clear       | C           | White       | W           |
| Bronze      | B           | Grey        | G           |

