

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on flat roofs, for mounting on curbs and flashing by others. Provides flexibility to obtain longer openings by joining two or more skylights in linear length.

- Custom sizes are available upon request



Model P-FF-BUTTED Available Sizes

Model #	Centerline Dimensions	Dome Colour	QTY
P-FF-BUTTED 3636	33½" x 33½" (845mm x 845mm)		
P-FF-BUTTED 4242	40" x 40" (1016mm x 1016mm)		
P-FF-BUTTED 5252	49¼" x 49¼" (1251mm x 1251mm)		
P-FF-BUTTED 6060	58" x 58" (1473mm x 1473mm)		
P-FF-BUTTED 7272	70" x 70" (1778mm x 1778mm)		
P-FF-BUTTED 8080	78" x 78" (1981mm x 1981mm)		
P-FF-BUTTED 9696	92½" x 92½" (2350mm x 2350mm)		
P-FF-BUTTED CUST.			

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Project:

Contractor:

Approved By:

Architect:

Date:

Specifications:

Skylight shall be factory assembled Model No. _____ P-FF-BUTTED as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic pyramids of clear, white, bronze, or grey. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber bulb draft seal. The retaining cap frame shall be extruded, mill finish, 6063-T5 aluminum alloy with heliarc welded corners. Mullions shall consist of 7" mill finish, extruded aluminum channel and pressure plate, 6063-T5 alloy, with santoprene gaskets. Structural and intermediate supports are supplied by others.

