

Artistic Skylights conform to and exceed test requirements of the following criteria:  
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1½" (38mm) with flashing (by others unless stated otherwise). These units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available



### Model G-PVCCM Available Sizes

| Model #       | B x B Dimensions              | Glazing Type | Flashing Kit y/n | QTY |
|---------------|-------------------------------|--------------|------------------|-----|
| G-PVCCM 2020  | 14¼" x 14¼" (362mm x 362mm)   |              |                  |     |
| G-PVCCM 2052  | 14¼" x 46¼" (362mm x 1175mm)  |              |                  |     |
| G-PVCCM 2828  | 22¼" x 22¼" (565mm x 565mm)   |              |                  |     |
| G-PVCCM 2836  | 22¼" x 30¼" (565mm x 768mm)   |              |                  |     |
| G-PVCCM 2852  | 22¼" x 46¼" (565mm x 1175mm)  |              |                  |     |
| G-PVCCM 2860  | 22¼" x 55" (565mm x 1397mm)   |              |                  |     |
| G-PVCCM 2876  | 22¼" x 69½" (565mm x 1765mm)  |              |                  |     |
| G-PVCCM 2896  | 22¼" x 89½" (565mm x 2273mm)  |              |                  |     |
| G-PVCCM 3636  | 30¼" x 30¼" (768mm x 768mm)   |              |                  |     |
| G-PVCCM 3642  | 30¼" x 37" (768mm x 940mm)    |              |                  |     |
| G-PVCCM 3652  | 30¼" x 46¼" (768mm x 1175mm)  |              |                  |     |
| G-PVCCM 3660  | 30¼" x 55" (768mm x 1397mm)   |              |                  |     |
| G-PVCCM 3676  | 30¼" x 69½" (768mm x 1765mm)  |              |                  |     |
| G-PVCCM 3696  | 30¼" x 89½" (768mm x 2273mm)  |              |                  |     |
| G-PVCCM 4242  | 37" x 37" (940mm x 940mm)     |              |                  |     |
| G-PVCCM 4252  | 37" x 46¼" (940mm x 1175mm)   |              |                  |     |
| G-PVCCM 4280  | 37" x 75" (940mm x 1905mm)    |              |                  |     |
| G-PVCCM 5252  | 46¼" x 46¼" (1175mm x 1175mm) |              |                  |     |
| G-PVCCM 5260  | 46¼" x 55" (1175mm x 1397mm)  |              |                  |     |
| G-PVCCM 5276  | 46¼" x 69½" (1175mm x 1765mm) |              |                  |     |
| G-PVCCM 6060  | 55" x 55" (1397mm x 1397mm)   |              |                  |     |
| G-PVCCM CUST. |                               |              |                  |     |
| G-PVCCM CUST. |                               |              |                  |     |

### Specifications:

Skylight shall be factory assembled Model No. \_\_\_\_\_ G-PVCCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear Low-E over clear. The skylight shall consist of a high-impact rigid extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to the exterior, and a co-extruded rubber draft seal. The retaining cap frame shall be of extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:

Contractor:

Architect:

Approved By:

Date:

### Glazing Available

| Glazing Type | Colour Code | Glazing Type    | Colour Code |
|--------------|-------------|-----------------|-------------|
| Clear/Low-E  | Low-E       | Clear/Laminated | Lami.       |
| Bronze/Low-E | B/Low-E     | Argon/Low-E     | Low-E/Arg   |

