

Artistic Skylights conform to and exceed test requirements of the following criteria:
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1½" (38mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available



Model PVCCM Available Sizes				
Model #	B x B Dimensions	Dome Colour	Flashing Kit y/n	QTY
PVCCM 2020	14¼" x 14¼" (362mm x 362mm)			
PVCCM 2052	14¼" x 46¼" (362mm x 1175mm)			
PVCCM 2828	22¼" x 22¼" (565mm x 565mm)			
PVCCM 2836	22¼" x 30¼" (565mm x 768mm)			
PVCCM 2852	22¼" x 46¼" (565mm x 1175mm)			
PVCCM 2860	22¼" x 55" (565mm x 1397mm)			
PVCCM 2876	22¼" x 69½" (565mm x 1765mm)			
PVCCM 2896	22¼" x 89½" (565mm x 2273mm)			
PVCCM 3636	30¼" x 30¼" (768mm x 768mm)			
PVCCM 3642	30¼" x 37" (768mm x 940mm)			
PVCCM 3652	30¼" x 46¼" (768mm x 1175mm)			
PVCCM 3660	30¼" x 55" (768mm x 1397mm)			
PVCCM 3676	30¼" x 69½" (768mm x 1765mm)			
PVCCM 3696	30¼" x 89½" (768mm x 2273mm)			
PVCCM 4242	37" x 37" (940mm x 940mm)			
PVCCM 4252	37" x 46¼" (940mm x 1175mm)			
PVCCM 4280	37" x 75" (940mm x 1905mm)			
PVCCM 5252	46¼" x 46¼" (1175mm x 1175mm)			
PVCCM 5260	46¼" x 55" (1175mm x 1397mm)			
PVCCM 5276	46¼" x 69½" (1175mm x 1765mm)			
PVCCM 5280	46¼" x 75" (1175mm x 1905mm)			
PVCCM 5296	46¼" x 89½" (1175mm x 2273mm)			
PVCCM 6060	55" x 55" (1397mm x 1397mm)			
PVCCM 6076	55" x 69½" (1397mm x 1765mm)			
PVCCM 6096	55" x 89½" (1397mm x 2273mm)			
PVCCM 7272	67" x 67" (1702mm x 1702mm)			
PVCCM 7296	67" x 89½" (1702mm x 2273mm)			
PVCCM CUST.				
PVCCM CUST.				

Specifications:

Skylight shall be factory assembled Model No. _____ PVCCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight shall consist of rigid high-impact extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to the exterior, co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Customer: _____

Job: _____

Model: _____

Dome Colours Available			
Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Quantity: _____

