

## Venting Dome Curb Mount Skylight (Sloped Roof)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1½" (38mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available

								opcomodiono.	
	Mode	I V-PVCCN	/I Avai	lable Sizes				Skylight shall be factory ass  No.  V-PVCCM as	
Model #	B x B Dimensions			Dome Colou	r F	lashing Kit	QTY	Skylight Domes Ltd. Vaugh	
V-PVCCM 2828	22¼" x 22¼"	(565mm x 565	imm)					consist of, sealed double a	
V-PVCCM 2836	22¼" x 30¼"	(565mm x 768	Bmm)					triple domes) of clear, white	
V-PVCCM 2852	22¼" x 46¼"	(565mm x 117	'5mm)					skylight incorporates a hea	
V-PVCCM 2860	22¼" x 55"	(565mm x 139	7mm)					chain drive operating mech	
V-PVCCM 2876	22¼" x 69½"	(565mm x 176	55mm)					system and removable inse	
V-PVCCM 3636	30¼" x 30¼"	(768mm x 768	Bmm)						
V-PVCCM 3642	30¼" x 37"	(768mm x 940	mm)					shall consist of rigid high-in	
V-PVCCM 3652	30¼" x 46¼"	(768mm x 117						frame (superior in thermal of	
V-PVCCM 3660	30¼" x 55"	(768mm x 139	7mm)					which incorporates a high of	
V-PVCCM 4242	37" x 37"	(940mm x 940	mm)					condensation gutter with dr	
V-PVCCM 4252	37" x 461/4"	(940mm x 117	'5mm)					co-extruded rubber draft se	
V-PVCCM 5252	46¼" x 46¼"	(1175mm x 11	75mm)					enamel extruded aluminum	
V-PVCCM CUST.								6063-T5. The retaining cap	
V-PVCCM CUST.								mill finish (optional baked e	
Dome Colours Available aluminum alloy with heliard									
Dome Colour Colour Co		our Code	Dome Colour		Colour Code		de	optional telescoping pole-h	
Clear C		С	White		W			system are available.	
Bronze		В		Grey	G			1	
Project:	·							Architect:	
Contractor: A			Approv	proved By:				Date:	



## Specifications:

ssembled Model s manufactured by Artistic han, Ontario. Glazing shall acrylic domes (or sealed ite, bronze, or grey. The avy-duty corrosion resistant chanism, pin pivot hinge sect screen. The skylight impact extruded vinyl curb conductivity to aluminum) capacity, 10 degree sloped drainage to exterior, seal and a white baked m sash frame, allov p frame shall be extruded, enamel), 6063-T5 c welded corners. An -hook or electric motorized

SEALED DOUBLE.  EXTRUDED ALUMINUM RETAINER CAP FRAME BUTYL RETAINER FRAME SEAL  BUTYL GLAZING SEAL  ASSEMBLY SCREW  EXTRUDED ALUMINUM SASH FRAME  RIGID BULB  (FLEXIBLE PVC-UV STABLE)  EXTRUDED RIGID VINYL CURB  MOUNT FRAME  ROOF MEMBRANES  METAL FLASHING  CURB		INSE I DRIVE OPERATING	MOVABLE ECT SCREEN  NSION
	1/2"		