

Artistic Skylights conform to and exceed test requirements of the following criteria:
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1½" (38mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available



Model G-PVCCM Available Sizes

Model #	B x B Dimensions	Glazing Type	Flashing Kit y/n	QTY
G-PVCCM 2020	14¼" x 14¼" (362mm x 362mm)			
G-PVCCM 2052	14¼" x 46¼" (362mm x 1175mm)			
G-PVCCM 2828	22¼" x 22¼" (565mm x 565mm)			
G-PVCCM 2836	22¼" x 30¼" (565mm x 768mm)			
G-PVCCM 2852	22¼" x 46¼" (565mm x 1175mm)			
G-PVCCM 2860	22¼" x 55" (565mm x 1397mm)			
G-PVCCM 2876	22¼" x 69½" (565mm x 1765mm)			
G-PVCCM 2896	22¼" x 89½" (565mm x 2273mm)			
G-PVCCM 3636	30¼" x 30¼" (768mm x 768mm)			
G-PVCCM 3642	30¼" x 37" (768mm x 940mm)			
G-PVCCM 3652	30¼" x 46¼" (768mm x 1175mm)			
G-PVCCM 3660	30¼" x 55" (768mm x 1397mm)			
G-PVCCM 3676	30¼" x 69½" (768mm x 1765mm)			
G-PVCCM 3696	30¼" x 89½" (768mm x 2273mm)			
G-PVCCM 4242	37" x 37" (940mm x 940mm)			
G-PVCCM 4252	37" x 46¼" (940mm x 1175mm)			
G-PVCCM 4280	37" x 75" (940mm x 1905mm)			
G-PVCCM 5252	46¼" x 46¼" (1175mm x 1175mm)			
G-PVCCM 5260	46¼" x 55" (1175mm x 1397mm)			
G-PVCCM 5276	46¼" x 69½" (1175mm x 1765mm)			
G-PVCCM 6060	55" x 55" (1397mm x 1397mm)			
G-PVCCM CUST.				
G-PVCCM CUST.				

Specifications:

Skylight shall be factory assembled Model No. _____ G-PVCCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear Low-E over clear. The skylight shall consist of a high-impact rigid extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to the exterior, and a co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:
Contractor:
Architect:
Approved By:
Date:

Glazing Available

Glazing Type	Colour Code	Glazing Type	Colour Code
Clear/Low-E	Low-E	Clear/Laminated	Lami.
Bronze/Low-E	B/Low-E	Argon/Low-E	Low-E/Arg

