

Artistic Skylights conform to and exceed test requirements of the following criteria:
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Fall Protection Series (FPS) Skylights are suitable for use on all type roofs. Designed for mounting on 1½" (38mm) curbs with flashing (by others), these units provide fall protection conforming to OSHA regulation CFR 1910.23(e)(8) Fall Impact Load Test for skylights. (Third party test report available.)

- Custom sizes are available upon request



Model FPS-FF Available Sizes

Model #	B x B Dimensions	Dome Colour	QTY
FPS-FF 2020	14¼" x 14¼" (362mm x 362mm)		
FPS-FF 2052	14¼" x 46¼" (362mm x 1175mm)		
FPS-FF 2828	22¼" x 22¼" (565mm x 565mm)		
FPS-FF 2836	22¼" x 30¼" (565mm x 768mm)		
FPS-FF 2852	22¼" x 46¼" (565mm x 1175mm)		
FPS-FF 2860	22¼" x 55" (565mm x 1397mm)		
FPS-FF 2876	22¼" x 69½" (565mm x 1765mm)		
FPS-FF 2896	22¼" x 89½" (565mm x 2273mm)		
FPS-FF 3636	30¼" x 30¼" (768mm x 768mm)		
FPS-FF 3642	30¼" x 37" (768mm x 940mm)		
FPS-FF 3652	30¼" x 46¼" (768mm x 1175mm)		
FPS-FF 3660	30¼" x 55" (768mm x 1397mm)		
FPS-FF 3676	30¼" x 69½" (768mm x 1765mm)		
FPS-FF 3696	30¼" x 89½" (768mm x 2273mm)		
FPS-FF 4242	37" x 37" (940mm x 940mm)		
FPS-FF 4252	37" x 46¼" (940mm x 1175mm)		
FPS-FF 4280	37" x 75" (940mm x 1905mm)		
FPS-FF 5252	46¼" x 46¼" (1175mm x 1175mm)		
FPS-FF 5260	46¼" x 55" (1175mm x 1397mm)		
FPS-FF 5276	46¼" x 69½" (1175mm x 1765mm)		
FPS-FF 5280	46¼" x 75" (1175mm x 1905mm)		
FPS-FF 5296	46¼" x 89½" (1175mm x 2273mm)		
FPS-FF 6060	55" x 55" (1397mm x 1397mm)		
FPS-FF 6076	55" x 69½" (1397mm x 1765mm)		
FPS-FF 6096	55" x 89½" (1397mm x 2273mm)		
FPS-FF 7272	67" x 67" (1702mm x 1702mm)		
FPS-FF 7296	67" x 89½" (1702mm x 2273mm)		
FPS-FF CUSTOM			

Specifications:

Skylight shall be factory assembled Model No. _____ FPS-FF as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of clear, sealed double Polycarbonate high impact domes (or sealed triple domes). The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber bulb draft seal. The retaining cap frame shall be extruded, mill finish, 6063-T5 aluminum alloy with heliarc welded corners. Domes to be sealed to frame with Silpruf High Strength Waterproofing Sealant & Structural Glazing Silicone.

Project:
Contractor:
Architect:
Approved By:
Date:

Dome Colours Available

Dome Colour	Colour Code
Clear	C

