



Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylight designed to be installed on flat roofs. These skylights come complete with insulated aluminum curb and mount directly over roof opening.

- Custom sizes are available upon request

#### Model CL Available Sizes

Model #	B x B Dimensions	Dome Colour	QTY
CL 2052	14¼" x 46¼" (362mm x 1175mm)		
CL 2828	22¼" x 22¼" (565mm x 565mm)		
CL 2836	22¼" x 30¼" (565mm x 768mm)		
CL 2852	22¼" x 46¼" (565mm x 1175mm)		
CL 2860	22¼" x 55" (565mm x 1397mm)		
CL 2876	22¼" x 69½" (565mm x 1765mm)		
CL 2896	22¼" x 89½" (565mm x 2273mm)		
CL 3636	30¼" x 30¼" (768mm x 768mm)		
CL 3642	30¼" x 37" (768mm x 940mm)		
CL 3652	30¼" x 46¼" (768mm x 1175mm)		
CL 3660	30¼" x 55" (768mm x 1397mm)		
CL 3676	30¼" x 69½" (768mm x 1765mm)		
CL 3696	30¼" x 89½" (768mm x 2273mm)		
CL 4242	37" x 37" (940mm x 940mm)		
CL 4252	37" x 46¼" (940mm x 1175mm)		
CL 4280	37" x 75" (940mm x 1905mm)		
CL 5252	46¼" x 46¼" (1175mm x 1175mm)		
CL 5260	46¼" x 55" (1175mm x 1397mm)		
CL 5276	46¼" x 69½" (1175mm x 1765mm)		
CL 5280	46¼" x 75" (1175mm x 1905mm)		
CL 5296	46¼" x 89½" (1175mm x 2273mm)		
CL 6060	55" x 55" (1397mm x 1397mm)		
CL 6076	55" x 69½" (1397mm x 1765mm)		
CL 6096	55" x 89½" (1397mm x 2273mm)		
CL 7272	67" x 67" (1702mm x 1702mm)		
CL 7296	67" x 89½" (1702mm x 2273mm)		
CL 8080	75" x 75" (1905mm x 1905mm)		
CL 9696	89½" x 89½" (2273mm x 2273mm)		
CL CUST.			
CL CUST.			

#### Specifications:

Skylight shall be factory assembled Model No. \_\_\_\_\_ CL as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight shall consist of rigid high-impac extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy (0.063" thick), with heliarc welded corners.

Curb shall be, 9" high (optional 12") mill finish aluminum, 2 piece construction of .050 outer wall and .050 inner wall, with 1½" thick insulation and 2' aluminum mounting flange.

Project:
Contractor:
Architect:
Approved By:
Date:

#### Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

