

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylight designed to be installed on flat roofs. These skylights come complete with insulated aluminum curb and mount directly over roof opening.

- Custom sizes are available upon request



Model T-CL Available Sizes

Model #	B x B Dimensions	Dome Colour	QTY
T-CL 2052	14 1/4" x 46 1/4" (362mm x 1175mm)		
T-CL 2828	22 1/4" x 22 1/4" (565mm x 565mm)		
T-CL 2836	22 1/4" x 30 1/4" (565mm x 768mm)		
T-CL 2852	22 1/4" x 46 1/4" (565mm x 1175mm)		
T-CL 2860	22 1/4" x 55" (565mm x 1397mm)		
T-CL 2876	22 1/4" x 69 1/2" (565mm x 1765mm)		
T-CL 2896	22 1/4" x 89 1/2" (565mm x 2273mm)		
T-CL 3636	30 1/4" x 30 1/4" (768mm x 768mm)		
T-CL 3642	30 1/4" x 37" (768mm x 940mm)		
T-CL 3652	30 1/4" x 46 1/4" (768mm x 1175mm)		
T-CL 3660	30 1/4" x 55" (768mm x 1397mm)		
T-CL 3676	30 1/4" x 69 1/2" (768mm x 1765mm)		
T-CL 3696	30 1/4" x 89 1/2" (768mm x 2273mm)		
T-CL 4242	37" x 37" (940mm x 940mm)		
T-CL 4252	37" x 46 1/4" (940mm x 1175mm)		
T-CL 4280	37" x 75" (940mm x 1905mm)		
T-CL 5252	46 1/4" x 46 1/4" (1175mm x 1175mm)		
T-CL 5260	46 1/4" x 55" (1175mm x 1397mm)		
T-CL 5276	46 1/4" x 69 1/2" (1175mm x 1765mm)		
T-CL 5280	46 1/4" x 75" (1175mm x 1905mm)		
T-CL 5296	46 1/4" x 89 1/2" (1175mm x 2273mm)		
T-CL 6060	55" x 55" (1397mm x 1397mm)		
T-CL 6076	55" x 69 1/2" (1397mm x 1765mm)		
T-CL 6096	55" x 89 1/2" (1397mm x 2273mm)		
T-CL 7272	67" x 67" (1702mm x 1702mm)		
T-CL 7296	67" x 89 1/2" (1702mm x 2273mm)		
T-CL 8080	75" x 75" (1905mm x 1905mm)		
T-CL 9696	89 1/2" x 89 1/2" (2273mm x 2273mm)		
T-CL CUST.			
T-CL CUST.			

Specifications:

Skylight shall be factory assembled Model No. _____ T-CL as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed triple acrylic domes of clear, white or bronze. The skylight shall consist of rigid high-impact extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners. Curb shall be, 9" high (optional 12") mill finish aluminum, 2 piece construction, with 1 1/2" thick insulation and 2" aluminum mounting flange.

Project:
Contractor:
Architect:
Approved By:
Date:

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

