

Artistic Skylights conform to and exceed test requirements of the following criteria:
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all type roofs. Designed for mounting on 1½" (38mm) or 4" (102mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Custom sizes are available upon request



| Model FF Available Sizes | | | |
|--------------------------|-------------------------------|-------------|-----|
| Model # | B x B Dimensions | Dome Colour | QTY |
| FF 2020 | 14¼" x 14¼" (362mm x 362mm) | | |
| FF 2052 | 14¼" x 46¼" (362mm x 1175mm) | | |
| FF 2828 | 22¼" x 22¼" (565mm x 565mm) | | |
| FF 2836 | 22¼" x 30¼" (565mm x 768mm) | | |
| FF 2852 | 22¼" x 46¼" (565mm x 1175mm) | | |
| FF 2860 | 22¼" x 55" (565mm x 1397mm) | | |
| FF 2876 | 22¼" x 69½" (565mm x 1765mm) | | |
| FF 2896 | 22¼" x 89½" (565mm x 2273mm) | | |
| FF 3636 | 30¼" x 30¼" (768mm x 768mm) | | |
| FF 3642 | 30¼" x 37" (768mm x 940mm) | | |
| FF 3652 | 30¼" x 46¼" (768mm x 1175mm) | | |
| FF 3660 | 30¼" x 55" (768mm x 1397mm) | | |
| FF 3676 | 30¼" x 69½" (768mm x 1765mm) | | |
| FF 3696 | 30¼" x 89½" (768mm x 2273mm) | | |
| FF 4242 | 37" x 37" (940mm x 940mm) | | |
| FF 4252 | 37" x 46¼" (940mm x 1175mm) | | |
| FF 4280 | 37" x 75" (940mm x 1905mm) | | |
| FF 5252 | 46¼" x 46¼" (1175mm x 1175mm) | | |
| FF 5260 | 46¼" x 55" (1175mm x 1397mm) | | |
| FF 5276 | 46¼" x 69½" (1175mm x 1765mm) | | |
| FF 5280 | 46¼" x 75" (1175mm x 1905mm) | | |
| FF 5296 | 46¼" x 89½" (1175mm x 2273mm) | | |
| FF 6060 | 55" x 55" (1397mm x 1397mm) | | |
| FF 6076 | 55" x 69½" (1397mm x 1765mm) | | |
| FF 6096 | 55" x 89½" (1397mm x 2273mm) | | |
| FF 7272 | 67" x 67" (1702mm x 1702mm) | | |
| FF 7296 | 67" x 89½" (1702mm x 2273mm) | | |
| FF 8080 | 75" x 75" (1905mm x 1905mm) | | |
| FF 9696 | 89½" x 89½" (2273mm x 2273mm) | | |
| FF CUST. | | | |
| FF CUST. | | | |

Specifications:

Skylight shall be factory assembled Model No. _____ FF as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber bulb draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel, 6063-T5 aluminum alloy with heliarc welded corners).

Project: _____

Contractor: _____

Architect: _____

Approved By: _____

Date: _____

| Dome Colours Available | | | |
|------------------------|-------------|-------------|-------------|
| Dome Colour | Colour Code | Dome Colour | Colour Code |
| Clear | C | White | W |
| Bronze | B | Grey | G |

