

Removable Frost-Free Commercial Curb Mount Skylight

Artistic Skylights conform to and exceed test requirements of the following criteria:
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all type roofs. Designed for mounting on 1½" (38mm) or 4" (102mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Custom sizes are available upon request



Model R-FF Available Sizes

Model #	Outside Curb Dimensions	Dome Colour	QTY
R-FF 2020	17¼" x 17¼" (438mm x 438mm)		
R-FF 2052	17¼" x 49¼" (438mm x 1251mm)		
R-FF 2828	25¼" x 25¼" (641mm x 641mm)		
R-FF 2836	25¼" x 33¼" (641mm x 844mm)		
R-FF 2852	25¼" x 49¼" (641mm x 1251mm)		
R-FF 2860	25¼" x 58" (641mm x 1473mm)		
R-FF 2876	25¼" x 72½" (641mm x 1842mm)		
R-FF 2896	25¼" x 92½" (641mm x 2349mm)		
R-FF 3636	33¼" x 33¼" (844mm x 844mm)		
R-FF 3642	33¼" x 40" (844mm x 1016mm)		
R-FF 3652	33¼" x 49¼" (844mm x 1251mm)		
R-FF 3660	33¼" x 58" (844mm x 1473mm)		
R-FF 3676	33¼" x 72½" (844mm x 1842mm)		
R-FF 3696	33¼" x 92½" (844mm x 2349mm)		
R-FF 4242	40" x 40" (1016mm x 1016mm)		
R-FF 4252	40" x 49¼" (1016mm x 1251mm)		
R-FF 4280	40" x 78" (1016mm x 1981mm)		
R-FF 5252	49¼" x 49¼" (1251mm x 1251mm)		
R-FF 5260	49¼" x 58" (1251mm x 1473mm)		
R-FF 5276	49¼" x 72½" (1251mm x 1842mm)		
R-FF 5280	49¼" x 78" (1251mm x 1981mm)		
R-FF 5296	49¼" x 92½" (1251mm x 2349mm)		
R-FF 6060	58" x 58" (1473mm x 1473mm)		
R-FF 6076	58" x 72½" (1473mm x 1842mm)		
R-FF 6096	58" x 92½" (1473mm x 2349mm)		
R-FF 7272	70" x 70" (1778mm x 1778mm)		
R-FF 7296	70" x 92½" (1778mm x 2349mm)		
R-FF 8080	78" x 78" (1981mm x 1981mm)		
R-FF 9696	92½" x 92½" (2349mm x 2349mm)		
R-FF CUST.			
R-FF CUST.			

Specifications:

Skylight shall be factory assembled Model No. _____ R-FF as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes of clear, white, or bronze. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break which incorporates a 10 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber bulb draft seal. The retaining cap frame shall be extruded, mill finish, 6063-T5 aluminum alloy with heliarc welded corners. Skylights complete with S.S. lockable catch, (locks and mounting by others).

Project: _____

Contractor: _____

Architect: _____

Approved By: _____

Date: _____

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B		

