

Artistic Skylights conform to and exceed test requirements of the following criteria:
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all type roofs. Designed for mounting on 3" (76mm) to 8" (200mm) wide curbs with flashing (by others), these units are specifically designed for retrofit and/or new applications alike. They provide excellent performance in all geographic locations.

- Custom sizes are available upon request



Model PC-FF Available Sizes

Model #	Outside Curb Dimensions	Dome Colour	QTY
PC-FF 2020	17¼" x 17¼" (435mm x 435mm)		
PC-FF 2052	17¼" x 49¼" (435mm x 1251mm)		
PC-FF 2828	25¼" x 25¼" (641mm x 641mm)		
PC-FF 2836	25¼" x 33¼" (641mm x 845mm)		
PC-FF 2852	25¼" x 49¼" (641mm x 1251mm)		
PC-FF 2860	25¼" x 58" (641mm x 1473mm)		
PC-FF 2876	25¼" x 72½" (641mm x 1842mm)		
PC-FF 2896	25¼" x 92½" (641mm x 2349mm)		
PC-FF 3636	33¼" x 33¼" (845mm x 845mm)		
PC-FF 3642	33¼" x 40" (845mm x 1016mm)		
PC-FF 3652	33¼" x 49¼" (845mm x 1251mm)		
PC-FF 3660	33¼" x 58" (845mm x 1473mm)		
PC-FF 3676	33¼" x 72½" (845mm x 1842mm)		
PC-FF 3696	33¼" x 92½" (845mm x 2349mm)		
PC-FF 4242	40" x 40" (1016mm x 1016mm)		
PC-FF 4252	40" x 49¼" (1016mm x 1251mm)		
PC-FF 4280	40" x 78" (1016mm x 1981mm)		
PC-FF 5252	49¼" x 49¼" (1251mm x 1251mm)		
PC-FF 5260	49¼" x 58" (1251mm x 1473mm)		
PC-FF 5276	49¼" x 72½" (1251mm x 1842mm)		
PC-FF 5280	49¼" x 78" (1251mm x 1981mm)		
PC-FF 5296	49¼" x 92½" (1251mm x 2349mm)		
PC-FF 6060	58" x 58" (1473mm x 1473mm)		
PC-FF 6076	58" x 72½" (1473mm x 1842mm)		
PC-FF 6096	58" x 92½" (1473mm x 2349mm)		
PC-FF 7272	70" x 70" (1778mm x 1778mm)		
PC-FF 7296	70" x 92½" (1778mm x 2349mm)		
PC-FF CUST.			
PC-FF CUST.			

Specifications:

Skylight shall be factory assembled Model No. _____ PC-FF as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed polycarbonate over acrylic domes (or polycarbonate over polycarbonate) of clear or bronze. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber bulb draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:
Contractor:
Architect:
Approved By:
Date:

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	Bronze	B

