

Circular Dome (Triple Glazed) Curb Mount Skylight with Aluminum Curb (Flat Roof)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on flat roofs. These skylights mount directly over roof opening and come complete with prefabricated, insulated aluminum curbs.

Custom sizes are available upon request



Model T-C Available Sizes				
Model #	B Diameter		Dome Colour	QTY
T-C 28	22½"	(572mm)		
T-C 36	30½"	(775mm)		
T-C 42	37"	(940mm)		
T-C 48	43"	(1092mm)		
T-C 52	46½"	(1181mm)		
T-C 60	55"	(1397mm)		
T-C 72	67"	(1702mm)		
T-C 80	75"	(1905mm)		
T-C 96	89½"	(2273mm)		
T-C CUST.				
Domo Colouro Available				

Dome Colours Available

Dome Colour Code Dome Colour Code

Clear C White W

Bronze B Grey G

Project: Architect:

Contractor: Approved By: Date:

Specifications:

Skylight shall be factory assembled Model No. T-C _____ as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed triple acrylic domes of clear, white, or bronze. Skylight shall consist of aluminum curb frame with thermal break and sloped condensation gutter with drainage to exterior. Retaining cap frame shall be mill finish, 6063-T5 aluminum alloy. Curb shall be 9" high (optional 12") mill finish aluminum, 2 piece construction of .050 outer wall and .050 inner wall, with 2" thick fiberglass insulation and 3" aluminum mounting flange.

