

Circular Dome Curb Mount Skylight with Aluminum Curb (Sloped Roof)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on flat roofs. These skylights mount directly over roof opening and come complete with prefabricated, insulated aluminum curbs.

Custom sizes are available upon request

							_		
Model C Available Sizes							Specifications:		
Model #	ВГ	Diameter	Dome Colour			QTY	Skylight shall be factory asse		
C 28	22½"	(572mm)							
C 36	30½"	(775mm)					Domes Ltd. Vaughan, Ontarion consist of, sealed double acrutriple domes) of clear, white,		
C 42	37"	(940mm)							
C 48	43"	(1092mm)							
C 52	46½"	46½" (1181mm) 55" (1397mm) 67" (1702mm)					skylight shall consist of alum thermal break and sloped co with drainage to exterior. Ret		
C 60	55"								
C 72	67"								
C 80	75"	(1905mm)					be mill finish, 6063-T5 alumir		
C 96	89½" (2273mm)						•		
C-CUST.							be 5" high mill finish aluminur		
Dome Colours Available							construction of .050 outer wa		
Dome Colour		Cold	our Code	Dome Colour	Colour Code		with 2" thick fiberglass insula mounting flange.		
Clear			С	White	W				
Bronze			В	Grey	G				
Project:							Architect:		
Contractor:				Approved By:			Date:		



embled Model No. ed by Artistic Skylight rio. Glazing shall crylic domes (or sealed , bronze, or grey. ninum curb frame with ondensation gutter etaining cap frame shall inum alloy. Curb shall um, 2 piece all and .050 inner wall, ation and 4" aluminum

