

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all type roofs. Designed for mounting on 1½" (38mm) or 4" (102mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Custom sizes are available upon request



Model P-FF (Ridge) Available Sizes			
Model #	B x B Dimensions	Pyramid Colour	QTY
P-FF 3660	30¼" x 55" (768mm x 1397mm)		
P-FF 4280	37" x 75" (940mm x 1905mm)		
P-FF 5260	46¼" x 55" (1175mm x 1397mm)		
P-FF 5276	46¼" x 69½" (1175mm x 1765mm)		
P-FF 5296	46¼" x 89½" (1175mm x 2273mm)		
P-FF 6076	55" x 69½" (1397mm x 1765mm)		
P-FF 7296	67" x 89½" (1702mm x 2273mm)		
P-FF CUST.			
P-FF CUST.			

### Pyramid Colours Available

Pyramid Colour	Colour Code	Pyramid Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Project:		Architect:
Contractor:	Approved By:	Date:

### Specifications:

Skylight shall be factory assembled Model No. \_\_\_\_\_ P-FF as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic pyramids (or sealed triple pyramids) of clear, white, bronze, or grey. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber bulb draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

