

E-Gress Frost-Free Roof Hatch Skylight (Sloped Roof)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on slope roofs. Designed for mounting on 1½" (38mm) curbs with flashing (by others), these units combine the natural light of standard skylights with the utility of roof access.

• Custom sizes are available upon request

Model HL-FF Available Sizes							
Model #	B x B Dimensions				Dome Colour		QTY
HL-FF 3636	30¼" x 30¼" (768mm x 768r			nm)			
HL-FF 3642	30¼" x 37" (768mm x 940r		nm)				
HL-FF 3652	30¼"	30¼" x 46¼" (768mm x 1175		imm)			
HL-FF 3676	30¼"	¼" x 69½" (768mm x 1765		imm)			
HL-FF 4242	37"	(0.1011111710101		nm)			
HL-FF 4252	37" x 46½" (940mm x 1175						
HL-FF 5252	46¼" x 46¼" (1175mm x 117			'5mm)			
HL-FF CUST.							
HL-FF CUST.							
Dome Colours Available							
Dome Colour		Colour Code		Dome Colour		Colour Code	
Clear		С		White		W	
Bronze		В		Grey		G	
Project:							
Contractor:			Approved By:				
Architect:			Date:				



Specifications:

Skylight shall be factory assembled Model HL-FF as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The hatch shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight shall have an extruded vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 8 degree sloped condensation gutter with drainage to exterior. The retaining cap frame shall be extruded, mill finish, 6063-T5 aluminum alloy with heliarc welded corners. This model is fully operational to 70 degrees, controlled by two #30 gas cylinders and grab handle. Hatch shall lock with two spring latch bolts.

